

## other commercial hardware



### Offset Handle (B2B)

**R13-S025450SS**

450 (C-C) x 25 x 25mm SSS

**R13-S025600SS**

600(C-C) x 25 x 25mm SSS



### Pull/-push Plates Plate Thickness 1.5mm D Handle 16mm dia

#### **PULL HANDLE**

**R13-EPP365200**

300 x 65mm w/200mm D-PULL  
(engraved)

**R13-PP310150**

300 x 100 w/150mm D-PULL

**R13-PP365150**

300 x 65 w/ 150mm D-PULL


#### **PUSH PLATES**

**R13-E365PUSS**

300 x 65mm (engraved with push)

**R13-365PUSS**

300 x 65mm (not engraved)



### SS Pull Handle (B2B)

**R13-32300DPHSS**

300 (C-C) x32mm

**R13-32600DPHSS**

600(C-C) x32mm



### SS Single Handle

**R13-SS16150SS**

150mm x 16 D-Pull SSS One Side Only

**R13-SS16200SS**

200mm x 16 D-Pull SSS One Side Only



### Push/Pull Plates with Concealed fix

**R13-CFPPSET**

One side 150mm x 16mm D-PULL  
w/ Plate 300 x 100mm  
Another side 300 x 100mm Plate  
with fixing legs  
SS Plate Thickness 2.0mm

introducing the  
**trio fire rated range**  
door closers | locks & levers



Please contact our sales staff on the number below  
for further information or to place an order.

Head Office: Trio Group  
494 Churchill Road, Kilburn North SA 5084  
Enquiries Ph: 08 8262 5055  
Fax Orders: 08 8262 5520  
sales@trioaustralia.com.au  
www.trioaustralia.com.au

Your local distributor:

 **TRIO** fire rated

## Door closers



### features

- Adjustable closing force, closing speed and latching action
- Adjustable backcheck
- Suitable for left and right hand doors
- Parallel arm bracket included
- For use on Firecore and Ecore doors

### fixing

- Suitable for standard fixing on the pull side and transom fixing on the push
- Suitable for parallel arm installation

### range and specifications

#### DC 3050

|  |
|--|
| <b>Max door leaf width:</b> 955mm          |
| <b>Max door height:</b> 2000-2400mm        |
| <b>Door weight up to:</b> 40-65kg          |
| <b>Max door opening angle approx:</b> 180° |
| <b>Closer spring size:</b> 3               |

#### DC 4080

|  |
|--|
| <b>Max door leaf width:</b> 1100mm         |
| <b>Max door height:</b> 2000-2400mm        |
| <b>Door weight up to:</b> 25-85kg          |
| <b>Max door opening angle approx:</b> 180° |
| <b>Closer spring size:</b> 2-4             |
| <b>Delayed Action Function</b>             |

#### DC 4080BL (Matte Black)

|  |
|--|
| <b>Max door leaf width:</b> 1100mm         |
| <b>Max door height:</b> 2000-2400mm        |
| <b>Door weight up to:</b> 25-85kg          |
| <b>Max door opening angle approx:</b> 180° |
| <b>Closer spring size:</b> 2-4             |
| <b>Delayed Action Function</b>             |

#### DC 5120

|  |
|--|
| <b>Max door leaf width:</b> 1400mm         |
| <b>Max door height:</b> 2000-2400mm        |
| <b>Door weight up to:</b> 40-150kg         |
| <b>Max door opening angle approx:</b> 180° |
| <b>Closer spring size:</b> 3-6             |
| <b>Delayed Action Function</b>             |

## Door locks



### features features

- Cylindrical chassis knob set
- Fire Rated 2 hours to AS1905. For use on Firecore and Ecore doors.
- Commercial Heavy Duty - Grade 2

### range and specifications

#### R21-K3007SS

##### Function: Entrance

Outside knob will become locked when inside button is pushed. To unlock, key must be used on outside knob which will release the inside knob. Inside knob is always unlocked providing emergency exit.

#### R21-K3062SS

##### Function: Storeroom

Outside knob always remains locked, requiring key opening to operate. Inside knob is always unlocked providing emergency exit.

#### R21-K3082SS

##### Function: Passage

Both outside and inside knobs always remain unlocked.



### specifications

- Satin Stainless Steel Finish
- CL series spherical knob set
- 70mm Backset (optional 60mm or 127mm)
- For door thickness: 35-50mm

#### R21-KL3007 (Knob/Lever)

##### Function: Entrance

Outside knob will become locked when inside button is pushed. To unlock, key must be used on outside knob which will release the inside lever. Inside lever is always unlocked providing emergency exit.

#### R21-K3095SS

##### Function: Storeroom

Knobs rigid at all times. Key retracts latch only from either side.

#### R21-KL3069SC

##### Function: Storeroom

Outside knob always remains locked, requiring key opening to operate. Inside lever is always unlocked providing emergency exit.

## Door levers



### features

- Cylindrical chassis lever set
- Fire Rated 2 hours to AS1905. For use on Firecore and Ecore doors.
- Commercial Heavy Duty - Grade 2

### range and specifications

#### R21-L8000SC

##### Function: Entrance

Outside lever will become locked when inside button is pushed. To unlock, key must be used on outside lever which will release the inside lever. Inside lever is always unlocked providing emergency exit.

#### R21-L8012SC

##### Function: Classroom

Outside lever is locked or unlocked by key. When locked, a key must be used from the outside to unlock the lockset. The inside lever is always unlocked providing emergency exit.

#### R21-L8052SC

##### Function: Connecting Room

Deadlocking latchbolt operates from the inside only. Blank plate outside.

#### R21-L8062SC

##### Function: Storeroom

Outside lever always remains locked, requiring key opening to operate. Inside lever is always unlocked providing emergency exit.

#### R21-L8082SC

##### Function: Passage

Both outside and inside levers always remain unlocked.



### specifications

- Satin Chrome & Matte Black Finish
- 70mm Backset (optional 60mm or 127mm)
- For door thickness: 35-50mm

#### R21-L8000MB (Matte Black)

##### Function: Entrance

Outside lever will become locked when inside button is pushed. To unlock, key must be used on outside lever which will release the inside lever. Inside lever is always unlocked providing emergency exit.

#### R21-L8062MB (Matte Black)

##### Function: Storeroom

Outside lever always remains locked, requiring key opening to operate. Inside lever is always unlocked providing emergency exit.

#### R21-L8011SC

##### Function: Classroom

Levers rigid at all times. Key retracts latch only from either side.

#### R21-L8030SC

##### Function: Privacy

Opened by handle when unlocked. Coin/screw driver unlocks external handle. Internal lever free to exit at all times. Internal push button locks exterior lever.

TRIO fire rated



## What is fire rated?

- To achieve maximum integrity of a fire door, the door furniture must withstand extreme heat conditions without fail. The Trio range has a 2 hour fire rating approval.

## When is fire rated used?

- The Building Code of Australia requires that new building construction have fire rating measures in place (either passive or active) to prevent the spread of flames and to minimise structural damage.

## Why use Trio?

- The Trio fire rated range has been tested to Australian Standards AS1905. and has a 2 hour approval.
- Trio's reputation and success has been based on delivering the highest level of quality products for the past 40 years.
- Suitable to suit all fire door sizes and designs.
- The Trio designs suit commercial applications, where maximum application durability is required, while also providing stylish designs.
- Available in Retail and Trade packaging to accommodate different market users.

TRIO  
ONE STOP  
Shop!